

What is claimed is:

1 1. A panel display apparatus for displaying an image in a
2 Subj A discharge sustain period, comprising:

3 a gas discharge panel in which a plurality of discharge cells
4 are arranged in the form of matrix between a pair of substrates;
5 and

6 a driving circuit which applies a write pulse to selected
7 discharge cells of the plurality of discharge cells to write the
8 image, and applies at least one sustain pulse to each of the
9 plurality of discharge cells to perform a sustain discharge in
10 the selected discharge cells,

11 wherein a pulse waveform of each sustain pulse is determined
12 so that a particular current waveform is formed when the sustain
13 pulse is applied, the particular current waveform being a
14 waveform in which a time from when a peak is reached to when a rise
15 fall is completed is no more than triple a time from when a rise
16 is started to when the peak is reached.

1 2. A panel display apparatus for displaying an image in a
2 discharge sustain period, comprising:

3 a gas discharge panel in which a plurality of discharge cells
4 are arranged in the form of matrix between a pair of substrates;
5 and

6 a driving circuit which applies a write pulse to selected
7 discharge cells of the plurality of discharge cells to write the
8 image, and applies at least one sustain pulse to each of the
9 plurality of discharge cells to perform a sustain discharge in
10 the selected discharge cells,

11 wherein immediately before a leading edge of each sustain
12 pulse which is applied to the discharge cell, the driving circuit
13 applies a pulse that is opposite in polarity to the sustain
14 pulse, to the discharge cell for a predetermined period.

3. The panel display apparatus of Claim 2,
wherein an absolute value of a voltage of the pulse that is
opposite in polarity to the sustain pulse is no smaller than an
absolute value of a voltage of the sustain pulse.

4. The panel display apparatus of Claim 3,
wherein a time during which the absolute value of the voltage
of the pulse is no smaller than the absolute value of the voltage
of the sustain pulse is no more than 100ns.

5. The panel display apparatus of Claim 3,
wherein a time during which the absolute value of the voltage
of the pulse is no smaller than the absolute value of the voltage

4. of the sustain pulse is no more than 50ns.

1. 6. The panel display apparatus of Claim 2,

2. wherein an absolute value of a voltage of the pulse that is
3. opposite in polarity to the sustain pulse is no smaller than 1.5
4. times an absolute value of a voltage of the sustain pulse.

1. 7. A panel display apparatus for displaying an image in a
2. discharge sustain period, comprising:

3. a gas discharge panel in which a plurality of discharge cells
4. are arranged in the form of matrix between a pair of substrates;
5. and

6. a driving circuit which (a) applies a write pulse to selected
7. discharge cells of the plurality of discharge cells to write the
8. image, and (b) successively applies a plurality of sustain pulses
9. which alternate in polarity, to each of the plurality of
10. discharge cells to perform a sustain discharge in the selected
11. discharge cells,

12. wherein immediately before a leading edge of at least a
13. sustain pulse of the plurality of sustain pulses which is first
14. applied to the discharge cell, the driving circuit applies a
15. pulse that is opposite in polarity to the sustain pulse, to the
16. discharge cell for a predetermined period.

1 8. The panel display apparatus of Claim 7,
2 wherein an absolute value of a voltage of the pulse that is
3 opposite in polarity to the sustain pulse is no smaller than an
4 absolute value of a voltage of the sustain pulse.

1 9. The panel display apparatus of Claim 8,
2 wherein a time during which the absolute value of the voltage
3 of the pulse is no smaller than the absolute value of the voltage
4 of the sustain pulse is no more than 100ns.

1 10. The panel display apparatus of Claim 8,
2 wherein a time during which the absolute value of the voltage
3 of the pulse is no smaller than the absolute value of the voltage
4 of the sustain pulse is no more than 50ns.

1 11. The panel display apparatus of Claim 7,
2 wherein an absolute value of a voltage of the pulse that is
3 opposite in polarity to the sustain pulse is no smaller than 1.5
4 times an absolute value of a voltage of the sustain pulse.

1 12. A panel display apparatus comprising:
2 a gas discharge panel in which a plurality of pairs of first

3 and second electrodes covered with a dielectric are arranged
4 between a pair of substrates; and

5 a driving circuit which accumulates a wall charge on the
6 dielectric to write an image, and applies at least one sustain
7 pulse between each pair of first and second electrodes to perform
8 a sustain discharge in areas where the wall charge has been
9 accumulated,

10 wherein immediately before a leading edge of each sustain
11 pulse which is applied between the pair of first and second
12 electrodes, the driving circuit applies a pulse that is opposite
13 in polarity to the sustain pulse, between the pair of first and
14 second electrodes for a predetermined period.

15 13. The panel display apparatus of Claim 12,

16 wherein the driving circuit applies the pulse of the opposite
17 polarity and the sustain pulse between the pair of first and
18 second electrodes, by applying two rectangular pulses that are
19 opposite in polarity, respectively to the first electrode and the
20 second electrode.

21 14. A panel display apparatus comprising:

22 a gas discharge panel in which a plurality of pairs of first
23 and second electrodes covered with a dielectric are arranged

4 between a pair of substrates; and

5 a driving circuit which (a) accumulates a wall charge on the
6 dielectric to write an image, and (b) successively applies a
7 plurality of sustain pulses which alternate in polarity, between
8 each pair of first and second electrodes to perform a sustain
9 discharge in areas where the wall charge has been accumulated,

10 wherein immediately before a leading edge of at least a
11 sustain pulse of the plurality of sustain pulses which is first
12 applied between the pair of first and second electrodes, the
13 driving circuit applies a pulse that is opposite in polarity to
14 the sustain pulse, between the pair of first and second
15 electrodes for a predetermined period.

16 15. A panel display apparatus for displaying an image in a
17 discharge sustain period, comprising:

18 a gas discharge panel in which a plurality of discharge cells
19 are arranged in the form of matrix between a pair of substrates;
20 and

21 a driving circuit which applies a write pulse to selected
22 discharge cells of the plurality of discharge cells to write the
23 image, and applies at least one sustain pulse to each of the
24 plurality of discharge cells to perform a sustain discharge in
25 the selected discharge cells,

11 wherein an absolute value of a voltage of each sustain pulse
12 which is applied to the discharge cell is higher during a first
13 period than a second period, the first period being a fixed
14 period from a leading edge of the sustain pulse, and the second
15 period being a period from a lapse of the fixed period to a
16 trailing edge of the sustain pulse.

1 16. The panel display apparatus of Claim 15,
2 wherein a highest absolute value of the voltage of the
3 sustain pulse in the first period exceeds an absolute value of a
4 discharge firing voltage of the discharge cell, and
5 the absolute value of the voltage of the sustain pulse in the
6 second period is below the absolute value of the discharge firing
7 voltage of the discharge cell.

1 17. The panel display apparatus of Claim 16,
2 wherein a time during which the absolute value of the voltage
3 of the sustain pulse exceeds the absolute value of the discharge
4 firing voltage is no more than 100ns.

1 18. The panel display apparatus of Claim 15,
2 wherein immediately after the trailing edge of the sustain
3 pulse, the driving circuit applies a pulse that is opposite in

4 polarity to the sustain pulse, to the discharge cell for a
5 predetermined period.

1 19. A panel display apparatus comprising:
2 a gas discharge panel in which a plurality of discharge cells
3 are arranged between a pair of substrates; and
4 a driving circuit which (a) applies a write pulse to selected
5 discharge cells of the plurality of discharge cells to write an
6 image, and (b) successively applies a plurality of sustain pulses
7 which alternate in polarity, to each of the plurality of
8 discharge cells to perform a sustain discharge in the selected
9 discharge cells,

10 wherein an absolute value of a voltage of at least a sustain
11 pulse of the plurality of sustain pulses which is first applied
12 to the discharge cell is higher during a first period than a
13 second period, the first period being a fixed period from a
14 leading edge of the sustain pulse, and the second period being a
15 period from a lapse of the fixed period to a trailing edge of the
16 sustain pulse.

1 20. The panel display apparatus of Claim 19,
2 wherein a highest absolute value of the voltage of the
3 sustain pulse in the first period exceeds an absolute value of a

4 discharge firing voltage of the discharge cell, and
5 the absolute value of the voltage of the sustain pulse in the
6 second period is below the absolute value of the discharge firing
7 voltage of the discharge cell.

1 21. The panel display apparatus of Claim 20,
2 wherein a time during which the absolute value of the voltage
3 of the sustain pulse exceeds the absolute value of the discharge
4 firing voltage is no more than 100ns.

1 22. The panel display apparatus of Claim 19,
2 wherein immediately after the trailing edge of the sustain
3 pulse, the driving circuit applies a pulse that is opposite in
4 polarity to the sustain pulse, to the discharge cell for a
5 predetermined period.

1 23. A panel display apparatus for displaying an image in a
2 discharge sustain period, comprising:
3 a gas discharge panel in which a plurality of discharge cells
4 are arranged in the form of matrix between a pair of substrates;
5 and
6 a driving circuit which applies a write pulse to selected
7 discharge cells of the plurality of discharge cells to write the

8 image, and applies at least one sustain pulse to each of the
9 plurality of discharge cells to perform a sustain discharge in
10 the selected discharge cells,

11 wherein immediately after a trailing edge of each sustain
12 pulse which is applied to the discharge cell, the driving circuit
13 applies a pulse that is opposite in polarity to the sustain
14 pulse, to the discharge cell for a predetermined period.

15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
259
260
261
262
263
264
265
266
267
268
269
269
270
271
272
273
274
275
276
277
278
279
279
280
281
282
283
284
285
286
287
288
289
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
309
310
311
312
313
314
315
316
317
318
319
319
320
321
322
323
324
325
326
327
328
329
329
330
331
332
333
334
335
336
337
338
339
339
340
341
342
343
344
345
346
347
348
349
349
350
351
352
353
354
355
356
357
358
359
359
360
361
362
363
364
365
366
367
368
369
369
370
371
372
373
374
375
376
377
378
379
379
380
381
382
383
384
385
386
387
388
389
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
409
410
411
412
413
414
415
416
417
418
419
419
420
421
422
423
424
425
426
427
428
429
429
430
431
432
433
434
435
436
437
438
439
439
440
441
442
443
444
445
446
447
448
449
449
450
451
452
453
454
455
456
457
458
459
459
460
461
462
463
464
465
466
467
468
469
469
470
471
472
473
474
475
476
477
478
479
479
480
481
482
483
484
485
486
487
488
489
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
509
510
511
512
513
514
515
516
517
518
519
519
520
521
522
523
524
525
526
527
528
529
529
530
531
532
533
534
535
536
537
538
539
539
540
541
542
543
544
545
546
547
548
549
549
550
551
552
553
554
555
556
557
558
559
559
560
561
562
563
564
565
566
567
568
569
569
570
571
572
573
574
575
576
577
578
579
579
580
581
582
583
584
585
586
587
588
589
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
609
610
611
612
613
614
615
616
617
618
619
619
620
621
622
623
624
625
626
627
628
629
629
630
631
632
633
634
635
636
637
638
639
639
640
641
642
643
644
645
646
647
648
649
649
650
651
652
653
654
655
656
657
658
659
659
660
661
662
663
664
665
666
667
668
669
669
670
671
672
673
674
675
676
677
678
679
679
680
681
682
683
684
685
686
687
688
689
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
709
710
711
712
713
714
715
716
717
718
719
719
720
721
722
723
724
725
726
727
728
729
729
730
731
732
733
734
735
736
737
738
739
739
740
741
742
743
744
745
746
747
748
749
749
750
751
752
753
754
755
756
757
758
759
759
760
761
762
763
764
765
766
767
768
769
769
770
771
772
773
774
775
776
777
778
779
779
780
781
782
783
784
785
786
787
788
789
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
809
810
811
812
813
814
815
816
817
818
819
819
820
821
822
823
824
825
826
827
828
829
829
830
831
832
833
834
835
836
837
838
839
839
840
841
842
843
844
845
846
847
848
849
849
850
851
852
853
854
855
856
857
858
859
859
860
861
862
863
864
865
866
867
868
869
869
870
871
872
873
874
875
876
877
878
879
879
880
881
882
883
884
885
886
887
888
889
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
909
910
911
912
913
914
915
916
917
918
919
919
920
921
922
923
924
925
926
927
928
929
929
930
931
932
933
934
935
936
937
938
939
939
940
941
942
943
944
945
946
947
948
949
949
950
951
952
953
954
955
956
957
958
959
959
960
961
962
963
964
965
966
967
968
969
969
970
971
972
973
974
975
976
977
978
979
979
980
981
982
983
984
985
986
987
988
989
989
990
991
992
993
994
995
996
997
998
999
1000

13 pulse that is opposite in polarity to the sustain pulse, to the
14 discharge cell for a predetermined period.

1 26. The panel display apparatus of Claim 25,
2 wherein the predetermined period is no more than 100ns.

1 27. A panel display apparatus comprising:
2 a gas discharge panel in which a plurality of pairs of first
3 and second electrodes covered with a dielectric are arranged
4 between a pair of substrates; and

5 a driving circuit which accumulates a wall charge on the
6 dielectric to write an image, and applies at least one sustain
7 pulse between each pair of first and second electrodes to perform
8 a sustain discharge in areas where the wall charge has been
9 accumulated,

10 wherein when applying each sustain pulse between the pair of
11 first and second electrodes, the driving circuit
12 applies a first voltage between the pair of first and second
13 electrodes for a fixed period from a leading edge of the sustain
14 pulse, and

15 applies a second voltage between the pair of first and second
16 electrodes for a period from a lapse of the fixed period to a
17 trailing edge of the sustain pulse, the second voltage having a

18 smaller absolute value than the first voltage.

1 28. The panel display apparatus of Claim 27,
2 wherein the driving circuit applies the first and second
3 voltages between the pair of first and second electrodes, by
4 applying two pulses that are same or opposite in polarity and
5 overlap in time, respectively to the first electrode and the
6 second electrode.

1 29. A panel display apparatus comprising:
2 a gas discharge panel in which a plurality of pairs of first
3 and second electrodes covered with a dielectric are arranged
4 between a pair of substrates; and
5 a driving circuit which accumulates a wall charge on the
6 dielectric to write an image, and applies at least one sustain
7 pulse between each pair of first and second electrodes to perform
8 a sustain discharge in areas where the wall charge has been
9 accumulated,
10 wherein immediately after a trailing edge of each sustain
11 pulse which is applied between the pair of first and second
12 electrodes, the driving circuit applies a pulse that is opposite
13 in polarity to the sustain pulse, between the pair of first and
14 second electrodes for a predetermined period.

1 30. The panel display apparatus of Claim 29,
2 wherein the driving circuit applies the sustain pulse and the
3 pulse of the opposite polarity between the pair of first and
4 second electrodes, by applying two pulses that are same in
5 polarity and overlap in time, respectively to the first electrode
6 and the second electrode.

1 31. A driving method for displaying an image in a discharge
2 sustain period in a gas discharge panel in which a plurality of
3 discharge cells are arranged between a pair of substrates,
4 comprising:

5 a writing step for applying a write pulse to selected
6 discharge cells of the plurality of discharge cells to write the
7 image; and

8 a discharge sustaining step for applying at least one sustain
9 pulse to each of the plurality of discharge cells to perform a
10 sustain discharge in the selected discharge cells,

11 wherein in the discharge sustaining step, immediately before
12 a leading edge of each sustain pulse which is applied to the
13 discharge cell, a pulse that is opposite in polarity to the
14 sustain pulse is applied to the discharge cell for a
15 predetermined period.

1 32. A driving method for displaying an image in a discharge
2 sustain period in a gas discharge panel in which a plurality of
3 discharge cells are arranged between a pair of substrates,
4 comprising:

5 a writing step for applying a write pulse to selected
6 discharge cells of the plurality of discharge cells to write the
7 image; and

8 a discharge sustaining step for successively applying a
9 plurality of sustain pulses which alternate in polarity, to each
10 of the plurality of discharge cells to perform a sustain
11 discharge in the selected discharge cells,

12 wherein in the discharge sustaining step, immediately before
13 a leading edge of at least a sustain pulse of the plurality of
14 sustain pulses which is first applied to the discharge cell, a
15 pulse that is opposite in polarity to the sustain pulse is
16 applied to the discharge cell for a predetermined period.

1 33. A driving method for displaying an image in a discharge
2 sustain period in a gas discharge panel in which a plurality of
3 discharge cells are arranged between a pair of substrates,
4 comprising:

5 a writing step for applying a write pulse to selected

6 discharge cells of the plurality of discharge cells to write the
7 image; and

8 a discharge sustaining step for applying at least one sustain
9 pulse to each of the plurality of discharge cells to perform a
10 sustain discharge in the selected discharge cells,

11 wherein in the discharge sustaining step, an absolute value
12 of a voltage of each sustain pulse which is applied to the
13 discharge cell is higher during a first period than a second
14 period, the first period being a fixed period from a leading edge
15 of the sustain pulse, and the second period being a period from
16 a lapse of the fixed period to a trailing edge of the sustain
17 pulse.

18 34. A driving method for displaying an image in a discharge
19 sustain period in a gas discharge panel in which a plurality of
20 discharge cells are arranged between a pair of substrates,
21 comprising:

22 a writing step for applying a write pulse to selected
23 discharge cells of the plurality of discharge cells to write the
24 image; and

25 a discharge sustaining step for applying at least one sustain
26 pulse to each of the plurality of discharge cells to perform a
27 sustain discharge in the selected discharge cells,

11 wherein in the discharge sustaining step, immediately after
12 a trailing edge of each sustain pulse which is applied to the
13 discharge cell, a pulse that is opposite in polarity to the
14 sustain pulse is applied to the discharge cell for a
15 predetermined period.